



GigaVUE Firewall Security Guide

GigaVUE

Product Version: 6.10

Document Version: 1.0

(See Change Notes for document updates.)

Copyright 2025 Gigamon Inc. All rights reserved.

Information in this document is subject to change without notice. The software described in this document is furnished under a license agreement or nondisclosure agreement. No part of this publication may be reproduced, transcribed, translated into any language, stored in a retrieval system, or transmitted in any form or any means without the written permission of Gigamon Inc.

Trademark Attributions

Gigamon and the Gigamon logo are trademarks of Gigamon in the United States and/or other countries. Gigamon trademarks can be found at www.gigamon.com/legal-trademarks. All other trademarks are the trademarks of their respective owners.

Gigamon Inc.
3300 Olcott Street
Santa Clara, CA 95054
408.831.4000

Change Notes

When a document is updated, the document version number on the cover page will indicate a new version and will provide a link to this Change Notes table, which will describe the updates.

Product Version	Document Version	Date Updated	Change Notes
6.10	1.0	03/07/2025	The original release of this document with 6.10.00 GA.

Contents

GigaVUE Firewall Security Guide	1
Change Notes	3
Contents	4
Get started with GigaVUE Security	5
Open Ports in GigaVUE-FM	5
GigaVUE-FM Open Ports	5
Open Ports for Communication Between Members of GigaVUE-FM High Availability Cluster	7
Open Ports for Communication Between Members of GigaVUE-FM High Availability Cluster	8
Network Firewall Requirement for GigaVUE Cloud Suite ..	10
Network Firewall Requirements for VMware vCenter	18
Network Firewall Requirements for VMware NSX-T	20
Network Firewall Requirements for Nutanix	22
Network Firewall Requirements for Gigamon Containerized Box	23
Additional Sources of Information	25
Documentation	25
How to Download Software and Release Notes from My Gigamon	27
Documentation Feedback	28
Contact Technical Support	29
Contact Sales	29
Premium Support	30
The VUE Community	30
Glossary	31

Get started with GigaVUE Security

This guide provides information about the open ports in GigaVUE-FM, GigaVUE-FM High Availability, open ports in GigaVUE HC Series devices, open ports in GigaVUE HC Series and GigaVUE TA Series devices.

You can also get information about the Network Firewall or Security Group for requirements for GigaVUE Cloud Suite deployment, Kubernetes network requirements for GCB.

Topics:

- [Open Ports in GigaVUE-FM](#)
- [Network Firewall Requirement for GigaVUE Cloud Suite](#)
- [Network Firewall Requirements for VMware vCenter](#)
- [Network Firewall Requirements for VMware NSX-T](#)
- [Network Firewall Requirements for Nutanix](#)
- [Network Firewall Requirements for Gigamon Containerized Box](#)

Open Ports in GigaVUE-FM

GigaVUE-FM Open Ports

The following table provides information about the ports.

Inbound

Protocol	Port Number	Service	Source CIDR	Purpose
TCP	22	SSH	Administrator Subnet	Allows CLI access to user-initiated management and diagnostics.
TCP	443	HTTPS	Administrator Subnet / GigaVUE-OS / Cloud Fabrics	Allows GigaVUE-FM to accept Management connection using REST API from user and Gigamon devices. Allows users to access GigaVUE-FM UI securely through an HTTPS connection.
TCP	514	Syslog	GigaVUE-OS Node	Allows GigaVUE-OS node to send syslog message to GigaVUE-FM over TCP.
UDP	514	Syslog	GigaVUE-OS Node	Allows GigaVUE-OS node to send syslog message to GigaVUE-FM over UDP.
UDP	162	SNMP	GigaVUE-OS Node	Allows GigaVUE-OS node to send SNMP events to GigaVUE-FM over UDP.
UDP	2056	FluentD	GigaVUE-OS Node / GigaVUE V Series	Allows GigaVUE-OS / GigaVUE V Series nodes to send Application Intelligence monitoring reports.
UDP	2096	FluentD	GigaVUE-OS Node	Allows GigaVUE-OS node to send Basic Inline SSL Session Stats.
UDP	2097	FluentD	GigaVUE-OS Node	Allows GigaVUE-OS node to send Advanced Inline SSL Session Stats.
TCP	5671	RabbitMq	Cloud Fabric Nodes	Allows Cloud Fabric nodes to send health events, solution status, statistics, and other notifications.
TCP	9600	StepCA	Cloud Fabric Nodes	Allows Cloud Fabric nodes to configure and renew the certificates.



Note:For FMHA, it is essential to open all the previously mentioned ports from GigaVUE-OS to every GigaVUE-FM node.

Outbound

Protocol	Port Number	Service	Source CIDR	Purpose
TCP	389	LDAP	GigaVUE-FM	Allows GigaVUE-FM to reach the LDAP server for authentication. Required only if the LDAP is configured for FM user authentication.
TCP	636	LDAP SSL	GigaVUE-FM	Allows GigaVUE-FM to reach the LDAP server over SSL for authentication. Required only if the LDAP is configured for FM user authentication.
UDP	1812	RADIUS (RFC 2865)	GigaVUE-FM	Allows GigaVUE-FM to reach the RADIUS server for authentication. Required only if the RADIUS is configured for FM user authentication.
UDP	1813	RADIUS (RFC 2866)	GigaVUE-FM	Allows GigaVUE-FM to reach the RADIUS server for authentication. Required only if the RADIUS is configured for FM user authentication..
UDP	49	TACACS	GigaVUE-FM	Allows GigaVUE-FM to reach the TACACS server for authentication. Required only if the TACACS is configured for FM user

Protocol	Port Number	Service	Source CIDR	Purpose
				authentication and TACACS uses TCP.
TCP	49	TACACS	GigaVUE-FM	Allows GigaVUE-FM to reach the TACACS server for authentication. Required only if the TACACS is configured for FM user authentication and TACACS uses TCP..
UDP	53	DNS	GigaVUE-FM	Allows GigaVUE-FM to reach the DNS server for name resolution.
UDP	68	DHCP	GigaVUE-FM	Allows GigaVUE-FM to reach the DHCP server for network configuration.
UDP	123	NTP	GigaVUE-FM	Allows GigaVUE-FM to reach the NTP server for time synchronization.

Open Ports for Communication Between Members of GigaVUE-FM High Availability Cluster

The following table lists the ports that must be open for communication between the members of GigaVUE-FM High Availability cluster.

NOTE: These ports cannot be accessed by standalone GigaVUE-FM instances.

Direction	Protocol	Port Number	Service	Source CIDR	Purpose
Bidirectional	TCP	443	HTTPS	GigaVUE-FM	REST API communication between HA members.
Bidirectional	TCP	8300	Consul	GigaVUE-FM	RPC communication between Consul members.
Bidirectional	TCP	8301	Consul	GigaVUE-FM	Heartbeat and Gossip between Consul members.
Bidirectional	UDP	8301	Consul	GigaVUE-FM	Heartbeat and Gossip between Consul members
Bidirectional	TCP	8302	Consul	GigaVUE-FM	Heartbeat and Gossip between Consul members over WAN.
Bidirectional	UDP	8302	Consul	GigaVUE-FM	Heartbeat and Gossip between Consul members over WAN.
Bidirectional	TCP	27071	MongoDB	GigaVUE-FM	Used for data replication across HA members and data access through GigaVUE-FM CLI.
Bidirectional	TCP	9300	OpenSearch	GigaVUE-FM	Used for data replication across cluster members.
Bidirectional	TCP	30865	CSync2	GigaVUE-FM	Used for the Synchronization of files / directories across HA members. For example, Image files during GigaVUE-FM HA Upgrade.
Bidirectional	TCP	24224	FluentD	GigaVUE-FM	Used for receiving/forwarding the packets from / to other HA members.
Bidirectional	UDP	24224	FluentD	GigaVUE-FM	Used for receiving/forwarding the packets from / to other HA members.

Network Firewall Requirement for GigaVUE Cloud Suite

The following table lists the Network Firewall / Security Group requirements for GigaVUE Cloud Suite.

NOTE: When using dual stack network, the below mentioned ports must be opened for both IPv4 and IPv6.

GigaVUE-FM				
Direction	Protocol	Port	Source CIDR	Purpose
Inbound	TCP	443	Administrator Subnet	Allows GigaVUE-FM to accept Management connection using REST API. Allows users to access GigaVUE-FM UI securely through an HTTPS connection.
Inbound	TCP	22	Administrator Subnet	Allows CLI access to user-initiated management and diagnostics.
Inbound (This is the port used for Third Party Orchestration)	TCP	443	UCT-V Controller IP	Allows GigaVUE-FM to receive registration requests from UCT-V Controller using REST API.
Inbound (This is the port used for Third Party Orchestration)	TCP	443	GigaVUE V Series Node IP	Allows GigaVUE-FM to receive registration requests from GigaVUE V Series Node using REST API when GigaVUE V Series Proxy is not used.
Inbound (This is the port used for Third Party Orchestration)	TCP	443	GigaVUE V Series Proxy IP	Allows GigaVUE-FM to receive registration requests from GigaVUE V Series Proxy using REST API.
Inbound	TCP	443	UCT-C Controller IP	Allows GigaVUE-FM to receive registration requests from UCT-C Controller using REST API.
Inbound	TCP	5671	GigaVUE V Series Node IP	Allows GigaVUE-FM to receive traffic health updates from GigaVUE V Series Nodes.

Inbound	TCP	5671	UCT-V Controller IP	Allows GigaVUE-FM to receive statistics from UCT-V Controllers.
Inbound	TCP	9600	UCT-V Controller	Allows GigaVUE-FM to receive certificate requests from UCT-V Controller.
Inbound	TCP	9600	GigaVUE V Series Proxy	Allows GigaVUE-FM to receive certificate requests from GigaVUE V Series Proxy.
Inbound	TCP	9600	GigaVUE V Series Node	Allows GigaVUE-FM to receive certificate requests from GigaVUE V Series Node.
Inbound	TCP	5671	UCT-C Controller IP	Allows GigaVUE-FM to receive statistics from UCT-C Controllers.
Inbound	UDP	2056	GigaVUE V Series Node IP	Allows GigaVUE-FM to receive Application Intelligence and Application Visualization reports from GigaVUE V Series Node.
Direction	Protocol	Port	Destination CIDR	Purpose
Outbound	TCP	9900	GigaVUE-FM IP	Allows GigaVUE-FM to communicate control and management plane traffic with UCT-V Controller.
Outbound (optional)	TCP	8890	GigaVUE V Series Proxy IP	Allows GigaVUE-FM to communicate control and management plane traffic to GigaVUE V Series Proxy.
Outbound	TCP	8889	GigaVUE V Series Node IP	Allows GigaVUE-FM to communicate control and management plane traffic to GigaVUE V Series Node.
Outbound	TCP	8443 (default)	UCT-C Controller IP	Allows GigaVUE-FM to communicate control and management plane traffic to UCT-C Controller.
Outbound	TCP	80	UCT-V Controller IP	Allows GigaVUE-FM to send ACME challenge requests to UCT-V Controller.
Outbound	TCP	80	GigaVUE V Series Node	Allows GigaVUE-FM to send ACME challenge requests to GigaVUE V Series Node.
Outbound	TCP	80	GigaVUE V Series Proxy	Allows GigaVUE-FM to send ACME challenge requests to GigaVUE V Series Proxy.

Outbound	TCP	443	Any IP Address	Allows GigaVUE-FM to reach the Public Cloud Platform APIs.
UCT-V Controller				
Direction	Protocol	Port	Source CIDR	Purpose
Inbound	TCP	9900	GigaVUE-FM IP	Allows UCT-V Controller to communicate control and management plane traffic with GigaVUE-FM
Inbound	TCP	9900	UCT-V or Subnet IP	Allows UCT-V Controller to receive traffic health updates from UCT-V.
Inbound	TCP	22	Administrator Subnet	Allows CLI access for user-initiated management and diagnostics, specifically when using third party orchestration.
Inbound	TCP	80	GigaVUE-FM	Allows UCT-V Controller to receive the ACME challenge requests from the GigaVUE-FM
Inbound	TCP	8300	UCT-V Subnet	Allows UCT-V Controller to receive the certificate requests from the UCT-V
Inbound (This is the port used for Third Party Orchestration)	TCP	8892	UCT-V Subnet	Allows UCT-V Controller to receive the registration requests and heartbeat from UCT-V.
Direction	Protocol	Port	Destination CIDR	Purpose
Outbound (This is the port used for Third Party Orchestration)	TCP	443	GigaVUE-FM IP	Allows UCT-V Controller to send the registration requests to GigaVUE-FM using REST API.
Outbound	TCP	5671	GigaVUE-FM IP	Allows UCT-V Controller to send traffic health updates to GigaVUE-FM.
Outbound (This is the port used for Third Party Orchestration)	TCP	9600	GigaVUE-FM IP	Allows GigaVUE-FM to receive certificate requests from the UCT-V Controller.
Outbound	TCP	9902	UCT-V Subnet	Allows UCT-V Controller to communicate control and management plane traffic with UCT-Vs for UCT-Vs with version greater than 6.10.00.

Outbound	TCP	8301	UCT-V Subnet	Allows ACME validation flow from UCT-V Controller to UCT-V.
UCT-V				
Direction	Protocol	Port	Source CIDR	Purpose
Inbound	TCP	9902	UCT-V Controller IP	Allows UCT-V to receive control and management plane traffic from UCT-V Controller
Inbound	TCP	8301	UCT-V Controller IP	Allows UCT-V to receive the ACME challenge requests from the UCT-V Controller
Direction	Protocol	Port	Destination CIDR	Purpose
Outbound	UDP (VXLAN)	VXLAN (default 4789)	GigaVUE V Series Node IP	Allows UCT-V to tunnel VXLAN traffic to GigaVUE V Series Nodes
Outbound	IP Protocol (L2GRE)	L2GRE (IP 47)	GigaVUE V Series Node IP	Allows UCT-V to tunnel L2GRE traffic to GigaVUE V Series Nodes
Outbound (Optional - This port is used only for Secure Tunnels)	TCP	11443	GigaVUE V Series Node IP	Allows UCT-V to securely transfer the traffic to the GigaVUE V Series Node
Outbound	TCP	9900	UCT-V Controller IP	Allows UCT-V to send traffic health updates to UCT-V Controller.
Outbound (This is the port used for Third Party Orchestration)	TCP	8892	UCT-V Controller IP	Allows UCT-V to receive the registration requests and heartbeat to UCT-V Controller.
Outbound	TCP	8300	UCT-V Controller IP	Allows UCT-V to receive ACME validation flow from UCT-V Controller
GigaVUE V Series Node				
Direction	Protocol	Port	Source CIDR	Purpose
Inbound	TCP	8889	GigaVUE-FM IP	Allows GigaVUE V Series Node to communicate control and management plane traffic with GigaVUE-FM
Inbound	TCP	8889	GigaVUE V Series Proxy IP	Allows GigaVUE V Series Node to communicate control and management

				plane traffic with GigaVUE V Series Proxy.
Inbound	UDP (VXLAN)	VXLAN (default 4789)	UCT-V Subnet IP	Allows GigaVUE V Series Nodes to receive VXLAN tunnel traffic to UCT-V
Inbound	IP Protocol (L2GRE)	L2GRE	UCT-V Subnet IP	Allows GigaVUE V Series Nodes to receive L2GRE tunnel traffic to UCT-V
Inbound	UDPGRE	4754	Ingress Tunnel	Allows GigaVUE V Series Node to receive tunnel traffic from UDPGRE Tunnel
Inbound	TCP	22	Administrator Subnet	Allows CLI access for user-initiated management and diagnostics, specifically when using third party orchestration.
Inbound	TCP	80	GigaVUE-FM	Allows GigaVUE V Series Node to receive the ACME challenge requests from the GigaVUE-FM
Inbound	TCP	80	GigaVUE V Series Proxy IP	Allows UCT-V to receive the ACME challenge requests from the GigaVUE V Series Proxy
Inbound (Optional - This port is used only for Secure Tunnels)	TCP	11443	UCT-V subnet	Allows to securely transfer the traffic to GigaVUE V Series Nodes.
Inbound (Optional - This port is used only for configuring AWS Gateway Load Balancer)	UDP (GENEVE)	6081	Ingress Tunnel	Allows GigaVUE V Series Node to receive tunnel traffic from AWS Gateway Load Balancer.
Direction	Protocol	Port	Destination CIDR	Purpose
Outbound	TCP	5671	GigaVUE-FM IP	Allows GigaVUE V Series Node to send traffic health updates to GigaVUE-FM.
Outbound	UDP (VXLAN)	VXLAN (default 4789)	Tool IP	Allows GigaVUE V Series Node to tunnel output to the tool.
Outbound	IP Protocol (L2GRE)	L2GRE (IP 47)	Tool IP	Allows GigaVUE V Series Node to tunnel output to the tool.
Outbound	UDP	2056	GigaVUE-FM IP	Allows GigaVUE V Series Node to send Application

				Intelligence and Application Visualization reports to GigaVUE-FM.
Outbound	UDP	2055	Tool IP	Allows GigaVUE V Series Node to send NetFlow Generation traffic to an external tool.
Outbound	UDP	8892	GigaVUE V Series Proxy	Allows GigaVUE V Series Node to send certificate request to GigaVUE V Series Proxy IP.
Outbound	TCP	514	Tool IP	Allows GigaVUE V Series Node to send Application Metadata Intelligence log messages to external tools.
Bidirectional (optional)	ICMP	<ul style="list-style-type: none"> • echo request • echo reply 	Tool IP	Allows GigaVUE V Series Node to send health check tunnel destination traffic.
Outbound (This is the port used for Third Party Orchestration)	TCP	443	GigaVUE-FM IP	Allows GigaVUE V Series Node to send registration requests and heartbeat messages to GigaVUE-FM when GigaVUE V Series Proxy is not used.
Outbound (Optional - This port is used only for Secure Tunnels)	TCP	11443	Tool IP	Allows to securely transfer the traffic to an external tool.
GigaVUE V Series Proxy (optional)				
Direction	Protocol	Port	Source CIDR	Purpose
Inbound	TCP	8890	GigaVUE-FM IP	Allows GigaVUE-FM to communicate control and management plane traffic with GigaVUE V Series Proxy.
Inbound	TCP	22	Administrator Subnet	Allows CLI access for user-initiated management and diagnostics, specifically when using third party orchestration.
Inbound	TCP	80	GigaVUE-FM	Allows GigaVUE V Series Proxy to receive the ACME challenge requests from the GigaVUE-FM
Inbound	TCP	8300	GigaVUE V Series Node	Allows GigaVUE V Series Proxy to receive certificate requests from GigaVUE V Series Node for the

				configured params and provides the certificate using those parameters.
Inbound	TCP	8892	GigaVUE V Series Node IP	Allows GigaVUE V Series Proxy to receive registration requests and heartbeat messages from GigaVUE V Series Node.
Direction	Protocol	Port	Destination CIDR	Purpose
Outbound	TCP	443	GigaVUE-FM IP	Allows GigaVUE V Series Proxy to communicate the registration requests to GigaVUE-FM
Outbound	TCP	8889	GigaVUE V Series Node IP	Allows GigaVUE V Series Proxy to communicate control and management plane traffic with GigaVUE V Series Node
Universal Cloud Tap - Container deployed inside Kubernetes worker node				
Direction	Protocol	Port	Destination CIDR	Purpose
Outbound	TCP	42042	Any IP address	Allows UCT-C to send statistical information to UCT-C Controller.
Outbound	UDP	VXLAN (default 4789)	Any IP address	Allows UCT-C to tunnel traffic to the GigaVUE V Series Node or other destination.
UCT-C Controller deployed inside Kubernetes worker node				
Direction	Protocol	Port	Source CIDR	Purpose
Inbound	TCP	8443 (configurable)	GigaVUE-FM IP	Allows GigaVUE-FM to communicate with UCT-C Controller.
Direction	Protocol	Port	Destination CIDR	Purpose
Outbound	TCP	5671	Any IP address	Allows UCT-C Controller to send statistics to GigaVUE-FM.
Outbound	TCP	443	GigaVUE-FM IP	Allows UCT-C Controller to communicate with GigaVUE-FM.

Ports to be opened for Backward Compatibility:

These ports must be opened for backward compatibility when GigaVUE-FM is running version 6.10 or later, and the fabric components are on (n-1) or (n-2) versions.

UCT-V Controller				
Direction	Protocol	Port	Source CIDR	Purpose
Inbound (This is the port used for Third Party Orchestration)	TCP	8891	UCT-V or Subnet IP	Allows UCT-V Controller to receive the registration requests from UCT-V.
Direction	Protocol	Port	Destination CIDR	Purpose
Outbound	TCP	9901	UCT-V Controller IP	Allows UCT-V Controller to communicate control and management plane traffic with UCT-Vs.
UCT-V				
Direction	Protocol	Port	Source CIDR	Purpose
Outbound (This is the port used for Third Party Orchestration)	TCP	8891	UCT-V Controller IP	Allows UCT-V to communicate with UCT-V Controller for registration and Heartbeat
GigaVUE V Series Node				
Direction	Protocol	Port	Source CIDR	Purpose
Outbound (This is the port used for Third Party Orchestration)	TCP	8891	GigaVUE V Series Proxy IP	Allows GigaVUE V Series Node to send registration requests and heartbeat messages to GigaVUE V Series Proxy when GigaVUE V Series Proxy is used.
GigaVUE V Series Proxy (optional)				
Direction	Protocol	Port	Source CIDR	Purpose
Inbound (This is the port used for Third Party Orchestration)	TCP	8891	GigaVUE V Series Node IP	Allows GigaVUE V Series Proxy to receive security parameter requests from GigaVUE V Series Node.

Network Firewall Requirements for VMware vCenter

Following are the Network Firewall Requirements for GigaVUE V Series Node deployment.

Source	Destination	Source Port	Destination Port	Protocol	Service	Purpose
GigaVUE-FM	ESXi hosts	Any (1024-65535)	443	TCP	https	Allows GigaVUE-FM to communicate with vCenter and all ESXi hosts to import the V Series OVA files. OVA files require access to the host IP/URL for bulk deployment
	vCenter					
GigaVUE-FM	GigaVUE V Series Nodes	Any (1024-65535)	8889	TCP	Custom API	Allows GigaVUE-FM to communicate with GigaVUE V Series Node
GigaVUE-FM	GigaVUE V Series Nodes	Any (1024-65535)	5671	TCP	Custom TCP	Allows GigaVUE-FM to receive the traffic health updates with GigaVUE V Series Node
GigaVUE-FM	GigaVUE V Series Nodes	Any (1024-65535)	80	TCP	Custom TCP	Allows GigaVUE-FM to send ACME challenge requests to GigaVUE V Series Node.
Administrator	GigaVUE-FM	Any (1024-65535)	443	TCP	https	Management connection to GigaVUE-FM
			22		ssh	
Administrator	GigaVUE V Series Nodes	Not Applicable	22		ssh	Troubleshooting GigaVUE V Series Nodes.

Remote Source	GigaVUE V Series Nodes	Custom Port (VXLAN and UDPGRE),N/A for GRE	4789	UDP	VXLAN	Allows to UDPGRE Tunnel to communicate and tunnel traffic to GigaVUE V Series Nodes (Applicable for Tunnel Ingress option only)
			N/A	IP 47	GRE	
			4754	UDP	UDPGRE	
GigaVUE V Series Nodes	Tool/ GiagVUE HC Series instance	Custom Port (VXLAN),N/A for GRE	4789	UDP	VXLAN	Allows GigaVUE V Series Node to communicate and tunnel traffic to the Tool
			Not Applicable	IP 47	GRE	
GigaVUE V Series Nodes	Tool/ GigaVUE HC Series instance	Not Applicable	Not Applicable	ICMP	Echo Request	Allows GigaVUE V Series Node to health check tunnel destination traffic (Optional)
					Echo Response	
GigaVUE V Series Nodes	GigaVUE-FM	Any (1024-65535)	Any (1024-65535)	TCP	Custom TCP	Allows GigaVUE V Series Nodes to communicate the traffic health updates with GigaVUE-FM
GigaVUE V Series Nodes	GigaVUE-FM	Any (1024-65535)	9600	TCP	Custom TCP	Allows GigaVUE-FM to receive certificate requests from GigaVUE V Series Node.

Network Firewall Requirements for VMware NSX-T

Following are the Network Firewall Requirements for GigaVUE V Series Node deployment.

Source	Destination	Source Port	Destination Port	Protocol	Service	Purpose
GigaVUE-FM	NSX-T Manager	Any (1024-65535)	443	TCP	https	Allows GigaVUE-FM to communicate with vCenter and NSX-T.
	vCenter					
GigaVUE-FM	GigaVUE V Series Node	Any (1024-65535)	8889	TCP	Custom API	Allows GigaVUE-FM to communicate with GigaVUE V Series Node
GigaVUE-FM	GigaVUE V Series Nodes	Any (1024-65535)	80	TCP	Custom TCP	Allows GigaVUE-FM to send ACME challenge requests to GigaVUE V Series Node.
Administrator	GigaVUE-FM	Any (1024-65535)	443	TCP	https	Management connection to GigaVUE-FM
			22		ssh	
Administrator	GigaVUE V Series Nodes	Not Applicable	22		ssh	Troubleshooting GigaVUE V Series Nodes.
GigaVUE-FM	GigaVUE V Series Node	Any (1024-65535)	5671	TCP	Custom TCP	Allows GigaVUE-FM to receive the traffic health updates with GigaVUE V Series Node

Remote Source	GigaVUE V Series Node	Custom Port (VXLAN and UDPGRE),N/A for GRE	4789	UDP	VXLAN	Allows to UDPGRE Tunnel to communicate and tunnel traffic to GigaVUE V Series Nodes (Applicable for Tunnel Ingress option only)
			N/A	IP 47	GRE	
			4754	UDP	UDPGRE	
GigaVUE V Series Node	Tool/ GigaVUE HC Series instance	Custom Port (VXLAN),N/A for GRE	4789	UDP	VXLAN	Allows GigaVUE V Series Node to communicate and tunnel traffic to the Tool
			N/A	IP 47	GRE	
GigaVUE V Series Node	Tool/ GigaVUE HC Series instance	N/A	N/A	ICMP	echo Request	Allows V Series node to health check tunnel destination traffic (Optional)
					echo Response	
GigaVUE V Series Node	GigaVUE-FM	Any (1024-65535)	5671	TCP	Custom TCP	Allows GigaVUE V Series Nodes to communicate the traffic health updates with GigaVUE-FM
GigaVUE V Series Nodes	GigaVUE-FM	Any (1024-65535)	9600	TCP	Custom TCP	Allows GigaVUE-FM to receive certificate requests from GigaVUE V Series Node.
GigaVUE-FM	External Image Server URL	Any (1024-65535)	Custom port on web Server	TCP	http	Access to image server to image lookup and checks, and downloading the image
NSX-T Manager						

vCenter						
NSX-T Manager	GigaVUE-FM	Any (1024-65535)	443	TCP	http	When using GigaVUE-FM as the image server for uploading the GigaVUE V Series Image.
vCenter						

Network Firewall Requirements for Nutanix

Following are the Network Firewall Requirements for GigaVUE Cloud Suite for Nutanix

Direction	Type	Protocol	Port	CIDR	Purpose
GigaVUE-FM					
Inbound	HTTPS	TCP	443	Anywhere Any IP	Allows GigaVUE® V Series Nodes, GigaVUE V Series Proxy, and GigaVUE-FM administrators to communicate with GigaVUE-FM
Inbound	SSH	TCP	22	Anywhere Any IP	Allows GigaVUE® V Series Nodes, GigaVUE V Series Proxy, and GigaVUE-FM administrators to communicate with GigaVUE-FM
Outbound (optional)	Custom TCP Rule	TCP	8890	GigaVUE V Series Proxy IP	Allows GigaVUE-FM to communicate with GigaVUE V Series Proxy
Outbound	Custom TCP Rule	TCP	8889	GigaVUE V Series Node IP	Allows GigaVUE-FM to communicate with GigaVUE V Series Node
Outbound	Custom TCP Rule	TCP	9440	Prism Central IP, Prism Element IP	Allows GigaVUE-FM to communicate with Prism Central and Prism Element.
GigaVUE V Series Node					
Inbound	Custom TCP Rule	TCP	9903	GigaVUE V Series Proxy IP	Allows GigaVUE V Series Proxy to communicate with GigaVUE® V Series Nodes

Direction	Type	Protocol	Port	CIDR	Purpose
Inbound	UDP	UDPGRE	4754	Ingress Tunnel	Allows to UDPGRE tunnel to communicate and tunnel traffic to GigaVUE V Series Nodes
Outbound	Custom TCP Rule	TCP	5671	GigaVUE-FM IP	Allows GigaVUE® V Series Node to communicate and tunnel traffic to the Tool
Outbound	Custom UDP Rule	<ul style="list-style-type: none"> UDP (VXLAN) IP Protocol (L2GRE) 	<ul style="list-style-type: none"> VXLAN (default 4789) L2GRE (IP 47) 	Tool IP	Allows GigaVUE® V Series Node to communicate and tunnel traffic to the Tool
Outbound (optional)	Custom ICMP Rule	ICMP	<ul style="list-style-type: none"> echo request echo reply 	Tool IP	Allows GigaVUE® V Series Node to health check the tunnel destination traffic.
GigaVUE V Series Proxy (optional)					
Inbound	Custom TCP Rule	TCP	8890	GigaVUE-FM IP	Allows GigaVUE-FM to communicate with GigaVUE V Series Proxy
Outbound	Custom TCP Rule	TCP	8889	GigaVUE V Series Node IP	Allows GigaVUE-FM to communicate with GigaVUE V Series Node

Network Firewall Requirements for Gigamon Containerized Box

Following are the Network Firewall Requirements for Gigamon Containerized Box (GCB).

Direction	Type	Protocol	Port	CIDR	Purpose
Gigamon Containerized Broker deployed inside Kubernetes worker node					
Outbound	HTTPS	TCP	443	Any IP address	Allows GCB Controller to communicate with GigaVUE-FM

Direction	Type	Protocol	Port	CIDR	Purpose
Inbound	HTTPS	TCP	8443 (configurable)	Any IP address	Allows GigaVUE-FM to communicate with GCB Controller.
Outbound	HTTPS	TCP	42042	Any IP address	Allows GCB to communicate with GigaVUE-FM to send statistics data.

Additional Sources of Information

This appendix provides additional sources of information. Refer to the following sections for details:

- [Documentation](#)
- [Documentation Feedback](#)
- [Contact Technical Support](#)
- [Contact Sales](#)
- [The VUE Community](#)

Documentation

This table lists all the guides provided for GigaVUE software and hardware. The first row provides an All-Documents Zip file that contains all the guides in the set for the release.

NOTE: In the online documentation, view [What's New](#) to access quick links to topics for each of the new features in this Release; view [Documentation Downloads](#) to download all PDFs.

Table 1: Documentation Set for Gigamon Products

GigaVUE 6.10 Hardware and Software Guides
<p>DID YOU KNOW? If you keep all PDFs for a release in common folder, you can easily search across the doc set by opening one of the files in Acrobat and choosing Edit > Advanced Search from the menu. This opens an interface that allows you to select a directory and search across all PDFs in a folder.</p>
<p>Hardware</p> <p>how to unpack, assemble, rackmount, connect, and initially configure ports the respective GigaVUE devices; reference information and specifications for the respective GigaVUE devices</p>
GigaVUE-HC1 Hardware Installation Guide
GigaVUE-HC3 Hardware Installation Guide
GigaVUE-HC1-Plus Hardware Installation Guide
GigaVUE-HCT Hardware Installation Guide
GigaVUE-TA25 Hardware Installation Guide
GigaVUE-TA25E Hardware Installation Guide
GigaVUE-TA100 Hardware Installation Guide
GigaVUE-TA200 Hardware Installation Guide

GigaVUE 6.10 Hardware and Software Guides

GigaVUE-TA200E Hardware Installation Guide

GigaVUE-TA400 Hardware Installation Guide

GigaVUE-OS Installation Guide for DELL S4112F-ON

G-TAP A Series 2 Installation Guide

GigaVUE M Series Hardware Installation Guide

GigaVUE-FM Hardware Appliances Guide

Software Installation and Upgrade Guides

GigaVUE-FM Installation, Migration, and Upgrade Guide

GigaVUE-OS Upgrade Guide

GigaVUE V Series Migration Guide

Fabric Management and Administration Guides

GigaVUE Administration Guide

covers both GigaVUE-OS and GigaVUE-FM

GigaVUE Fabric Management Guide

how to install, deploy, and operate GigaVUE-FM; how to configure GigaSMART operations; covers both GigaVUE-FM and GigaVUE-OS features

GigaVUE Application Intelligence Solutions Guide

Cloud Guides

how to configure the GigaVUE Cloud Suite components and set up traffic monitoring sessions for the cloud platforms

GigaVUE V Series Applications Guide

GigaVUE Cloud Suite Deployment Guide - AWS

GigaVUE Cloud Suite Deployment Guide - Azure

GigaVUE Cloud Suite Deployment Guide - OpenStack

GigaVUE Cloud Suite Deployment Guide - Nutanix

GigaVUE Cloud Suite Deployment Guide - VMware (ESXi)

GigaVUE Cloud Suite Deployment Guide - VMware (NSX-T)

GigaVUE Cloud Suite Deployment Guide - Third Party Orchestration

Universal Cloud TAP - Container Deployment Guide

Gigamon Containerized Broker Deployment Guide

GigaVUE 6.10 Hardware and Software Guides	
GigaVUE Cloud Suite Deployment Guide - AWS Secret Regions	
GigaVUE Cloud Suite Deployment Guide - Azure Secret Regions	
Reference Guides	
GigaVUE-OS CLI Reference Guide	library of GigaVUE-OS CLI (Command Line Interface) commands used to configure and operate GigaVUE HC Series and GigaVUE TA Series devices
GigaVUE-OS Security Hardening Guide	
GigaVUE Firewall and Security Guide	
GigaVUE Licensing Guide	
GigaVUE-OS Cabling Quick Reference Guide	guidelines for the different types of cables used to connect Gigamon devices
GigaVUE-OS Compatibility and Interoperability Matrix	compatibility information and interoperability requirements for Gigamon devices
GigaVUE-FM REST API Reference in GigaVUE-FM User's Guide	samples uses of the GigaVUE-FM Application Program Interfaces (APIs)
Factory Reset Guidelines for GigaVUE-FM and GigaVUE-OS Devices	Sanitization guidelines for GigaVUE Fabric Management Guide and GigaVUE-OS devices.
Release Notes	
GigaVUE-OS, GigaVUE-FM, GigaVUE-VM, G-TAP A Series, and GigaVUE Cloud Suite Release Notes	new features, resolved issues, and known issues in this release ; important notes regarding installing and upgrading to this release
	NOTE: Release Notes are not included in the online documentation.
	NOTE: Registered Customers can log in to My Gigamon to download the Software and Release Notes from the Software and Docs page on to My Gigamon . Refer to How to Download Software and Release Notes from My Gigamon .
In-Product Help	
GigaVUE-FM Online Help	how to install, deploy, and operate GigaVUE-FM.

How to Download Software and Release Notes from My Gigamon

Registered Customers can download software and corresponding Release Notes documents from the **Software & Release Notes** page on to [My Gigamon](#). Use the My Gigamon Software & Docs page to download:

- Gigamon Software installation and upgrade images,
- Release Notes for Gigamon Software, or
- Older versions of PDFs (pre-v5.7).

To download release-specific software, release notes, or older PDFs:

1. Log in to [My Gigamon](#).
2. Click on the **Software & Release Notes** link.
3. Use the **Product** and **Release** filters to find documentation for the current release. For example, select Product: "GigaVUE-FM" and Release: "5.6," enter "pdf" in the search box, and then click **GO** to view all PDF documentation for GigaVUE-FM 5.6.xx.

NOTE: My Gigamon is available to registered customers only. Newer documentation PDFs, with the exception of release notes, are all available through the publicly available online documentation.

Documentation Feedback

We are continuously improving our documentation to make it more accessible while maintaining accuracy and ease of use. Your feedback helps us to improve. To provide feedback and report issues in our documentation, send an email to:

documentationfeedback@gigamon.com

Please provide the following information in the email to help us identify and resolve the issue. Copy and paste this form into your email, complete it as able, and send. We will respond as soon as possible.

Documentation Feedback Form		
About You	Your Name	
	Your Role	
	Your Company	
For Online Topics	Online doc link	<i>(URL for where the issue is)</i>
	Topic Heading	<i>(if it's a long topic, please provide the heading of the section where the issue is)</i>

For PDF Topics	Document Title	<i>(shown on the cover page or in page header)</i>
	Product Version	<i>(shown on the cover page)</i>
	Document Version	<i>(shown on the cover page)</i>
	Chapter Heading	<i>(shown in footer)</i>
	PDF page #	<i>(shown in footer)</i>
How can we improve?	Describe the issue	<i>Describe the error or issue in the documentation. (If it helps, attach an image to show the issue.)</i>
	How can we improve the content? Be as specific as possible.	
	Any other comments?	

Contact Technical Support

For information about Technical Support: Go to **Settings**  > **Support** > **Contact Support** in GigaVUE-FM.

You can also refer to <https://www.gigamon.com/support-and-services/contact-support> for Technical Support hours and contact information.

Email Technical Support at support@gigamon.com.

Contact Sales

Use the following information to contact Gigamon channel partner or Gigamon sales representatives.

Telephone: +1.408.831.4025

Sales: inside.sales@gigamon.com

Partners: www.gigamon.com/partners.html

Premium Support

Email Gigamon at inside.sales@gigamon.com for information on purchasing 24x7 Premium Support. Premium Support entitles you to round-the-clock phone support with a dedicated Support Engineer every day of the week.

The VÜE Community

The **VÜE Community** is a technical site where Gigamon users, partners, security and network professionals and Gigamon employees come together to share knowledge and expertise, ask questions, build their network and learn about best practices for Gigamon products.

Visit the VÜE Community site to:

- Find knowledge base articles and documentation
- Ask and answer questions and learn best practices from other members.
- Join special-interest groups to have focused collaboration around a technology, use-case, vertical market or beta release
- Take online learning lessons and tutorials to broaden your knowledge of Gigamon products.
- Open support tickets (Customers only)
- Download the latest product updates and documentation (Customers only)

The VÜE Community is a great way to get answers fast, learn from experts and collaborate directly with other members around your areas of interest.

Register today at community.gigamon.com

Questions? Contact our Community team at community@gigamon.com.

Glossary

D

decrypt list

need to decrypt (formerly blacklist)

decryptlist

need to decrypt - CLI Command (formerly blacklist)

drop list

selective forwarding - drop (formerly blacklist)

F

forward list

selective forwarding - forward (formerly whitelist)

L

leader

leader in clustering node relationship (formerly master)

M

member node

follower in clustering node relationship (formerly slave or non-master)

N

no-decrypt list

no need to decrypt (formerly whitelist)

nodecryptlist

no need to decrypt- CLI Command (formerly whitelist)

P

primary source

root timing; transmits sync info to clocks in its network segment (formerly grandmaster)

R

receiver

follower in a bidirectional clock relationship (formerly slave)

S

source

leader in a bidirectional clock relationship (formerly master)